


# TRAILER CABLE



Stranded Bare  
Copper Conductors  
with PVC, Rubber  
or TPR Insulation

Twisted with  
Overall Jacket

60°C, 90°C, 105°C  
-40°C, -65°C

## APPLICATIONS Suitable for use as follows:

- Used for electrical connections between tractor and trailer unit

## CONSTRUCTION

- Stranded bare or tinned copper; paper separator
- PVC, EVA, XLPE, or EPDM insulation
- Twisted with polypropylene or paper fillers or available without fillers
- Overall PVC, EVA, or CPE compound
- Available in a variety of colors depending on compound
- Stranded bare copper conductors with PVC, rubber or TPR insulation
- Twisted with overall jacket

## WEIGHTS, MEASUREMENTS AND PACKAGING

NO. OF COND.	CABLE STYLE	INDIVIDUAL CONDUCTOR	INSULATION THICKNESS		JACKET THICKNESS		NOMINAL OVERALL DIAMETER	
			mm	inches	mm	inches	mm	inches
2	20	19	0	0	4.17	.164	35.01	23.53
3	20	19	0	0	4.5	.177	46.77	31.43
7	20	10	0	0	6.25	.246	106.72	71.72
2	18	16	0	0	6.6	.26	56.09	37.69
6	18	16	.64	.025	9.02	.355	138.56	93.12
4	16	19	0	0	8.38	.33	98.53	66.22
4	16	26	0	0	11.05	.435	172.83	116.15
5	16	19	.58	.023	9.02	.355	117.27	78.81
6	16	19	1.4	.055	10.16	.4	165.51	111.23
6	16	19	.58	.023	9.14	.36	123.99	83.33
2	14	19	.76	.03	7.92	.312	84.28	56.64
4	14	19	2.01	.079	11.3	.445	193.57	130.09
4	14	19	.76	.03	9.53	.375	172.55	115.96
4	14	41	0	0	11.43	.45	202.93	136.38
5	14	19	0	0	12.7	.5	239.98	161.28
5	14	19	1.12	.044	11.3	.445	210.51	141.47
6	14	19	1.4	.055	12.7	.5	256.88	172.64
7	14	19	0	0	16.26	.64	460.14	309.23
7	12	19	1.4	.055	14.73	.58	391.92	263.39
3	12	19	0	0	12.7	.5	229.91	154.51
4	12	19	1.09	.043	11.94	.47	248.66	167.11
5	12	19	0	0	12.7	.5	296.34	199.15
7	12	65	1.91	.075	13.79	.543	302.81	203.5
7	12	65	1.78	.07	13.79	.543	315.53	212.05
7	12	65	1.91	.075	13.79	.543	303.58	204.02
6	10	19	.97	.038	13.97	.55	337.83	227.04
7	10	19	2.34	.092	17.4	.685	460.18	309.26
7	10	19	1.07	.042	13.97	.55	353.95	237.87
7	10	104	1.91	.075	14.83	.584	393.61	264.52
7	8	161	1.78	.07	17.78	.7	530.41	356.46
7	8	161	2.29	.09	17.27	.68	490.97	329.96
7	8	161	1.52	.06	17.27	.68	511.13	343.5

Most trailer cables are manufactured to customer specifications. Data shown is a sample of available products. Any configuration is available upon request.

Standard Color Code: 4 Conductor: Red, Yellow, Green, Brown

6 Conductor: Red, Yellow, Black, White, Green, Brown

7 Conductor: Red, Yellow, Black, White, Green, Brown, Blue