

-20°C to +60°C, UNDERGROUND LOW ENERGY CIRCUIT CABLE 30VAC


APPLICATIONS

- Outdoor Low-Voltage Underground Landscape Lighting Cable is designed for landscape, security, and outdoor lighting applications that not to exceed 30 volts.
- Landscape Lighting Cable suitable for Direct Burial Stranded Copper Conductor Black PVC Insulation/Jacket.

CONSTRUCTION

- Two fully annealed bare stranded copper conductors
- Insulation/Jacket: Premium-grade PVC -20°C to +60°C
- Final assembly: Insulated/Jacketed conductors duplexed in a flat construction for easy tear-down during installation
- Color: Black

STANDARDS

UL Underground Low-Energy Circuit Cable for Outdoor Lighting
 Meets UL Subj 1493
 EU RoHS Directive

LEGEND:
 SOUTHWIRE xx AWG x/C UNDERGROUND LOW ENERGY CIRCUIT CABLE 60C 30VAC



Stock #	DESCRIPTION	AWG	#COND	NOM. OVERALL DIA. (inches)	WEIGHT (lb/100ft)	WALL THICKNESS (MIL)
55266	ULEC 16/2 STR CU BK	16	2	0.277	30.66	20
55267	ULEC 12/2 STR CU BK	14	2	0.318	42.6	20
55269	ULEC 14/2 STR CU BK	12	2	0.388	62.64	38.5
55272	ULEC 10/2 STR CU BK	10	2	0.382	85.6	30
55271	ULEC 8/2 STR CU BK	8	2	0.546	150.7	60

Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2019 Southwire Company, LLC. All Rights Reserved



Southwire®

Date: 8/28/2020