

## EZ-IN™ MINI-SPLIT CABLE

Temperature Rating: 90°C (Dry) and 75°C (Wet), 600V, Rated Sunlight Resistant and Direct Burial



**APPLICATION**

Southwire's armored mini-split cable can be installed in accordance with The National Electrical Code for HVAC applications without the use of conduit and may be installed indoors or outdoors in wet locations.

**TOOLS**

- Using appropriate Southwire tools for mini-split installations to reduce the chance of damage to internal wires See Tool Kit

**CONSTRUCTION**

- Conductor(s): Stranded, bare copper Class B, Soft Drawn Annealed Bare Copper per ASTM B3 and B8
- Insulation: Polyvinyl Chloride (PVC)/Nylon
- Armoring: Aluminum Interlocked Armor (AIA)
- Jacket: Black, PVC

**SPECIFICATIONS:**

- ASTM B3, B8
- UL 83 - Thermoplastic Insulated Wires and Cables
- UL 1569 - Metal-Clad Cables
- NFPA 70
- RoHS-3

Stock #	Description	AWG	Solid Stranded	#COND	Jacket COLOR	CONDUCTOR COLOR	OVERALL DIAMETER (mils)	NET WEIGHT (lbs/1000 ft)
586288	16/4 TFN AIA PVC EZ-IN Mini-Split 600V	16	Stranded	4	7	Black, Red, White, Green	562	137
583408	14/4 THHN AIA PVC EZ-IN Mini-Split 600V	14	Stranded	4	7	Black, Red, White, Green	553	148
583410	14/7 STR CU THHN AIA MC MINI-SPLIT JKT 600V	14	Stranded	7	7	Black, Red, Blue, Orange, Yellow, Brown, Red-Black	678	237