

MC^{AP}®

Type MC All Purpose



14 AWG through 8 AWG Copper THHN Insulated Conductors. Full-Sized Aluminum Equipment Grounding/Bonding Conductor. UL Listed. 600 Volt. Rated VW1. Lightweight Aluminum Interlocked Armor is Part of Equipment Bonding/Grounding Path.

APPLICATIONS

Southwire MC^{AP}® Type MC Cable - All Purpose is suitable for use as follows:

- Wherever standard AC or MC Cable is permitted.
- Branch circuit wiring in commercial, industrial, institutional, and multi-residential buildings.
- Fished or embedded in plaster.
- Concealed or exposed installations.
- Environmental air-handling spaces per NEC 300.22 (C).
- Places of Assembly per NEC 518.4 and theaters per NEC 520.5.
- Installation in cable tray and approved raceways.
- Under raised floors for information technology equipment conductors and cables per NEC 645.5(D) & 645.5(D)(2).
- Use UL Listed Type MCI-A connectors

STANDARDS & REFERENCES

Southwire MC^{AP}® Type MC Cable meets or exceeds the following:

- UL 83
- UL 1569
- UL 1063
- UL Online Product Guide Info - Metal-Clad Cable (PJAZ) (www.ul.com)
- NFPA 70 (National Electrical Code), Article 330
- Federal Specification A-A59544 (formerly J-C-30B)
- FT4/IEEE 1202 (70,000 Btu/hr) Vertical Cable Tray Flame Test
- Listed for use in UL 1, 2, and 3 Hour Through-Penetration Firestop Systems
- REACH/RoHS-2 (Chemical Limit) Compliant

CONSTRUCTION

Southwire MC^{AP}® Type MC Cable is constructed with solid soft-drawn copper Type THHN circuit conductors rated 90° C dry and a full-sized bare 8000 Series aluminum grounding/bonding conductor. This cable is available in sizes 14-8 AWG. The insulated conductors are cabled together and wrapped with a binder tape bearing the print legend. The bare aluminum grounding/bonding conductor is located outside the binding tape and has the same lay as the insulated conductors. Aluminum interlocking armor is snugly applied over the assembly. The aluminum armor and bare aluminum conductor are in intimate contact and together form the equipment ground path. To insure proper installation, refer to the installation instructions provided with every reel and coil.



MC^{AP}® Type MC All Purpose

CONDUCTOR SIZE AND COLORS	GROUNDING/BONDING CONDUCTOR	STOCK NUMBER		WEIGHT (LBS/1000')	OVERALL DIAMETER (INCHES)
		COIL (250')	REEL (1000')		
SOLID CONDUCTOR COLORS 120/208V					
14-2 SOLID (BLACK/WHITE)	12 SOLID ALUMINUM	55-52-72-01	55-52-72-02	63	.375
14-3 SOLID (BLACK/WHITE/RED)	12 SOLID ALUMINUM	55-52-73-01	55-52-73-02	81	.406
14-4 SOLID (BLACK/WHITE/RED/BLUE)	12 SOLID ALUMINUM	55-52-74-01	55-52-74-02	98	.435
12-2 SOLID (BLACK/WHITE)	10 SOLID ALUMINUM	55-51-03-01	55-51-03-02	86	.43
12-2 SOLID (RED/WHITE)	10 SOLID ALUMINUM	55-87-68-01	55-87-68-02	86	.43
12-2 SOLID (BLUE/WHITE)	10 SOLID ALUMINUM	55-87-70-01	55-87-70-02	86	.43
12-3 SOLID (BLACK/WHITE/RED)	10 SOLID ALUMINUM	55-51-04-01	55-51-04-02	111	.447
12-4 SOLID (BLACK/WHITE/RED/BLUE)	10 SOLID ALUMINUM	55-51-05-01	55-51-05-02	137	.48
10-2 SOLID (BLACK/WHITE)	8 SOLID ALUMINUM	55-52-75-01	55-52-75-02	124	.485
10-3 SOLID (BLACK/WHITE/RED)	8 SOLID ALUMINUM	55-52-77-01	55-52-77-02	164	.52
10-4 SOLID (BLACK/WHITE/RED/BLUE)	8 SOLID ALUMINUM	55-52-78-01	55-52-78-02	204	.565
STRANDED CONDUCTOR COLORS 120/208V					
12-2 STRANDED (BLACK/WHITE)	10 SOLID ALUMINUM	55-63-77-01	55-63-77-02	90	.437
12-2 STRANDED (RED/WHITE)	10 SOLID ALUMINUM	55-87-86-01	55-87-86-02	90	.437
12-2 STRANDED (BLUE/WHITE)	10 SOLID ALUMINUM	55-87-88-01	55-87-88-02	90	.437
12-3 STRANDED (BLACK/WHITE/RED)	10 SOLID ALUMINUM	55-64-57-01	55-64-57-02	118	.468
12-4 STRANDED (BLACK/WHITE/RED/BLUE)	10 SOLID ALUMINUM	55-58-74-01	55-58-74-01	145	.506
10-2 STRANDED (BLACK/WHITE)	8 SOLID ALUMINUM	55-73-87-01	55-73-87-02	130	.508
10-3 STRANDED (BLACK/WHITE/RED)	8 SOLID ALUMINUM	55-73-90-01	55-73-90-02	173	.548
SOLID CONDUCTOR COLORS 277/480V					
12-2 SOLID (YELLOW/GRAY)	10 SOLID ALUMINUM	55-55-39-01	55-55-39-02	86	.43
12-2 SOLID (BROWN/GRAY)	10 SOLID ALUMINUM	55-57-26-01	55-57-26-02	86	.43
12-2 SOLID (ORANGE/GRAY)	10 SOLID ALUMINUM	55-55-38-01	55-55-38-02	86	.43
12-3 SOLID (BROWN/YELLOW/GRAY)	10 SOLID ALUMINUM	55-55-41-01	55-55-41-02	111	.447
12-3 SOLID (BROWN/ORANGE/GRAY)	10 SOLID ALUMINUM	55-57-28-01	55-57-28-02	111	.447

The Power of Connections.™



Southwire®

©2016 Southwire Company, LLC. All rights reserved. *Registered Trademark of Southwire Company, LLC.
One Southwire Drive, Carrollton, GA 30119, USA

MC^{AP}® Type MC All Purpose

12-4 SOLID (BROWN/ORANGE/YELLOW/GRAY)	10 SOLID ALUMINUM	55-57-31-01	55-57-31-02	137	.48
10-2 SOLID (BROWN/GRAY)	8 SOLID ALUMINUM	55-57-33-01	55-57-33-02	124	.485
10-3 SOLID (BROWN/ORANGE/GRAY)	8 SOLID ALUMINUM	55-57-35-01	55-57-35-02	164	.52
10-4 SOLID (BROWN/ORANGE/YELLOW/GRAY)	8 SOLID ALUMINUM	55-57-37-01	55-57-37-01	204	.565
STRANDED CONDUCTOR COLORS 277/480V					
12-2 STRANDED (YELLOW/GRAY)	10 SOLID ALUMINUM	55-87-93-01	55-87-93-02	90	.437
12-2 STRANDED (BROWN/GRAY)	10 SOLID ALUMINUM	55-87-43-01	55-87-43-02	90	.437
12-2 STRANDED (ORANGE/GRAY)	10 SOLID ALUMINUM	55-87-90-01	55-87-90-02	90	.437
12-3 STRANDED (BROWN/ORANGE/GRAY)	10 SOLID ALUMINUM	55-87-45-01	55-87-45-02	118	.468
12-4 STRANDED (BROWN/ORANGE/YELLOW/GRAY)	10 SOLID ALUMINUM	55-87-47-01	55-87-47-02	145	.506
For allowable ampacities, refer to NEC 310.15. Dimensions are nominal and subject to normal manufacturing tolerances and should be used for reference purposes only.					

FEATURES

- An armor assembly that is an equipment grounding conductor per NEC 250.118(10)(b).
- Installation instructions included with every reel and coil.
- Simplified product application and installation over other armored products.
- Faster conductor make-up, wiring device installation and trim-out when grounding/bonding conductor is terminated per installation instructions.
- Reduces installation costs up to 50% over pipe and wire.
- UL Classified 1, 2, and 3 hour Through Penetration Firestop Systems: W-J-3037, W-L-3110, W-L-3113, W-L-3117, W-L-3120, W-L-3121, W-L-3160, C-AJ-3115, C-AJ-3140, C-AJ-3142, C-AJ-3145, C-AJ-3173, C-AJ-3202, C-AJ-4065, C-AJ-4066, F-C-3038.
- Cable reverse wound on reel for ease of pulling and installation. When pulling from coils, pull from inside to ensure ease of installation.
- Anti-short bushings are not required for use with MC cable per the NEC and UL

The Power of Connections.™



Southwire®

©2016 Southwire Company, LLC. All rights reserved. *Registered Trademark of Southwire Company, LLC.
One Southwire Drive, Carrollton, GA 30119, USA

NEC TABLE 310.15(B)(16)- ALLOWABLE AMPACITY FOR 600V CONDUCTORS

SIZE AWG OR KCMIL	TEMPERATURE RATING OF CONDUCTOR		
	60°C (140°F)	75°C (167°F)	90°C (194°F)
	Types: TW, UF	Types: RHW, THHW, THW, THWN, XHHW, USE, ZW	Types: TBS, SA, SIS, RHH, RHW-2, THHN, THHW, THW-2, THWN- 2, USE-2, XHH, XHHW, XHHW-2, ZW-2
COPPER			
18	-	-	14
16	-	-	18
14	15	20	25
12	20	25	30
10	30	35	40
8	40	50	55
6	55	65	75
4	70	85	95
3	85	100	115
2	95	115	130
1	110	130	145
1/0	125	150	170
2/0	145	175	195
3/0	165	200	225
4/0	195	230	260
250	215	255	290
300	240	285	320
350	260	310	350
400	280	335	380
500	320	380	430
600	350	420	475
700	385	460	520
750	400	475	535
800	410	490	555
900	435	520	585
1000	455	545	615
1250	495	590	665
1500	525	625	705
1750	545	650	735
2000	555	665	750
Per NEC 310.15(B)(5), the ampacity of 4/C cables shall be reduced by a factor of 0.80 when the neutral is considered a current-carrying conductor.			

Table is reprinted from NFPA 70-2014, the National Electric Code, © 2013 National Fire Protection Association, Quincy, Massachusetts 02269. This reprinted material is not the complete and official position of the National Fire Protection Association on the referenced subject, which is represented only by the standard in its entirety.