


COPPER TRACER WIRE


BLUE INSULATION




RED INSULATION




ORANGE INSULATION



BLACK INSULATION



GREEN INSULATION



APPLICATIONS

- Used as tracer wire to locate buried conduit
- 30 volt constructions suitable for direct burial
- 30 or 600 volt depending on insulation thickness

INDUSTRY APPROVALS

Southwire's soft-drawn copper tracer wire meets or exceeds the following ASTM specifications:

- B 3: Soft or Annealed copper wire
- UL listed as tracer wire

CONSTRUCTION








- Soft drawn copper solid conductor
- 16 AWG to 8 AWG
- Insulated with high molecular weight polyethylene (HMWPE)
- Color options: yellow, blue, red, orange, black, green

Soft Drawn Copper Wire

UL Listed

Insulated with HMWPE

Color Options Available:
Yellow, Blue, Red,
Orange, Black, Green

		COLOR OPTIONS	
CONDUIT	Fiber Optic Cable	orange	
	CATV/Telephone	orange	
	Gas	yellow	
	Electric	black, red	 
	Water	blue	
	Sewer	green	
	COLORS		



WEIGHTS AND MEASUREMENTS				
SIZE (AWG)	CONDUCTOR NOMINAL O.D. (inch)	INSULATION THICKNESS (inch)	OVERALL NOMINAL O.D. (inch)	APPROX. WEIGHT (lbs/1000 ft)
30 VOLTS				
16	.0508	0.030	0.111	11
14	.0641	0.030	0.124	16
12	.0808	0.030	0.141	24
10	.1019	0.030	0.162	36
8	.1280	0.030	0.189	56
600 VOLTS				
16	.0508	0.045	0.141	13
14	.0641	0.045	0.154	19
12	.0808	0.045	0.171	27
10	.1019	0.045	0.192	40
8	.1280	0.045	0.219	60