


# FLAT JACKETED HEAVY DUTY TYPE THW



PUMP  
CABLE



**Water Well Cable**

**600 Volt**

**Rated 75°C**

**Stranded Copper Conductors**

**Moisture Resistant PVC Insulation**

**Flat Parallel Configuration**

**Black PVC Jacket**

## APPLICATIONS

Suitable for use as follows:

- For use in residential, farm and industrial water well applications
- Grounded and ungrounded water well cable systems

## CONSTRUCTION

- Premium 600 volt cable featuring stranded copper conductors with a moisture resistant PVC insulation
- Conductors are individually colored black, red, and yellow with green ground
- Insulated conductors are assembled parallel in a flat configuration and covered with a tough, black thermoplastic jacket

## STANDARDS & REFERENCES

- Industry standard for electrical submersible pumping (ESP) water systems
- Meets NEC® code for submersible pump grounding requirements
- UL Standard 83
- UL Type THW Conductors

## FEATURES

- Sequential footage marking on flat jacketed and parallel cables

## WEIGHTS, MEASUREMENTS AND PACKAGING

SIZE (AWG) AND NUMBER OF CONDUCTORS	CONDUCTOR STRANDING (inch)	INSULATION NOMINAL THICKNESS (inch)	NOMINAL CABLE	
			DIMENSIONS (inch)	APPROX. WEIGHT (lbs/1000 ft)
<b>WITH GROUND</b>				
14/2 W/14 GR	7 STR × 0.0242	0.045	0.260 × 0.595	113
14/3 W/14 GR	7 STR × 0.0242	0.045	0.260 × 0.765	149
12/2 W/12 GR	19 STR × 0.0185	0.045	0.282 × 0.660	150
12/3 W/12 GR	19 STR × 0.0185	0.045	0.282 × 0.850	193
10/2 W/10 GR	19 STR × 0.0234	0.045	0.310 × 0.730	195
10/3 W/10 GR	19 STR × 0.0234	0.045	0.310 × 0.940	258
8/2 W/10 GR	19 STR × 0.0295	0.060	0.370 × 0.850	268
8/3 W/10 GR	19 STR × 0.0295	0.060	0.370 × 1.120	347
6/3 W/8 GR	19 STR × 0.0372	0.060	0.410 × 1.295	510
4/3 W/8 GR	19 STR × 0.0469	0.060	0.460 × 1.447	699
2/3 W/6 GR	19 STR × 0.0591	0.060	0.515 × 1.656	1022
1/0-3 W/6 GR	19 STR × 0.3730	0.080	0.660 × 2.130	1458
2/0-3 W/6 GR	19 STR × 0.4200	0.080	0.680 × 2.160	1845
<b>WITHOUT GROUND</b>				
10/2	19 STR × 0.0234	0.045	0.310 × 0.515	133
10/3	19 STR × 0.0234	0.045	0.310 × 0.730	195
8/3	19 STR × 0.0295	0.060	0.370 × 0.910	299
6/3	19 STR × 0.0372	0.060	0.410 × 1.025	411
4/3	19 STR × 0.0469	0.060	0.460 × 1.177	589
2/3	19 STR × 0.0591	0.060	0.515 × 1.350	866